

Appendix: Complete Listing of Claims

We claim:

Claim 1 (original): A heat exchanger for transferring heat between a first fluid and a second fluid; wherein said heat exchanger comprises first fluid channels through which the first fluid may flow, and second fluid channels through which the second fluid may flow, wherein said second fluid channels lie generally in a plane; wherein said first fluid channels and said second fluid channels interleave, so that heat may be transferred between said first fluid channels and said second fluid channels; wherein the direction of flow of said first fluid channels is generally perpendicular to the plane of said second fluid channels; and wherein said heat exchanger has a density of said first fluid channels greater than about 50 per square centimeter.

113
Claim 2 (original): A heat exchanger as recited in Claim 1, wherein said first fluid channels are adapted for the flow of a gas, and wherein said second fluid channels are adapted for the flow of a liquid.

Claim 3 (original): A heat exchanger as recited in Claim 1, wherein the thickness of said heat exchanger, in the direction of flow of said first fluid channels, is less than about 2.0 mm.

Claim 4 (original): A heat exchanger as recited in Claim 1, wherein the thickness of said heat exchanger, in the direction of flow of said first fluid channels, is less than about 1.0 mm.

Claim 5 (original): A heat exchanger as recited in Claim 1, wherein the width of said second fluid channels, in a direction that is generally perpendicular to the direction of flow of said first fluid channels and is also generally perpendicular to the direction of flow of said second fluid channels, is less than about 500 μm .

Claim 6 (original): A heat exchanger as recited in Claim 1, wherein said heat exchanger has a density of said first fluid channels greater than about 200 per square centimeter.

193
ent
Claim 7 (original): A heat exchanger as recited in Claim 1, wherein the thickness of said heat exchanger, in the direction of flow of said first fluid channels, is less than about 1.0 mm; wherein the width of said second fluid channels, in a direction that is generally perpendicular to the direction of flow of said first fluid channels and is also generally perpendicular to the direction of flow of said second fluid channels, is less than about 500 μm ; and wherein said heat exchanger has a density of said first fluid channels greater than about 200 per square centimeter.

Claim 8 (original): A heat exchanger as recited in Claim 1, wherein said heat exchanger is fabricated from a polymer.

Claim 9 (original): A heat exchanger as recited in Claim 1, wherein said heat exchanger is fabricated from a ceramic.

Claim 10 (original): A heat exchanger as recited in Claim 1, wherein said heat exchanger is fabricated from copper.

Claim 11 (original): A heat exchanger as recited in Claim 1, wherein said heat exchanger is fabricated from aluminum.

Claim 12 (original): A heat exchanger as recited in Claim 1, wherein said heat exchanger is fabricated from metal.

Claim 13 (original): A heat exchanger as recited in Claim 1, wherein the thickness of said heat exchanger, in the direction of flow of said first fluid channels, is less than about 6.0 mm.

113
cont

Claim 14 (original): A heat exchanger as recited in Claim 1, wherein the width of said second fluid channels, in a direction that is generally perpendicular to the direction of flow of said first fluid channels and is also generally perpendicular to the direction of flow of said second fluid channels, is less than about 2.0 mm.

Claim 15 (original): A heat exchanger as recited in Claim 1, wherein the thickness of said heat exchanger, in the direction of flow of said first fluid channels, is less than about 6.0 mm, and wherein the width of said second fluid channels, in a direction that is generally perpendicular to the direction of flow of said first fluid channels and is also generally perpendicular to the direction of flow of said second fluid channels, is less than about 2.0 mm.

Claim 16 (original): A heat exchanger for transferring heat between a first fluid and a second fluid; wherein said heat exchanger comprises first fluid channels through which the first fluid may flow, and one or more second, multiply interconnected fluid channels through which the second fluid may flow; wherein said first fluid channels and said second fluid channels interleave, so that heat may be transferred between said first fluid channels and said second fluid channels; wherein the direction of flow of said first fluid channels is generally perpendicular to the direction of flow of said second fluid channels; wherein the thickness of said heat exchanger, in the direction of flow of said first fluid channels, is less than about 6.0 mm; and wherein said heat exchanger has a density of said first fluid channels greater than about 50 per square centimeter.

13
u
Claim 17 (original): A heat exchanger as recited in Claim 16, wherein said first fluid channels are adapted for the flow of a gas, and wherein said second fluid channels are adapted for the flow of a liquid.

Claim 18 (original): A heat exchanger as recited in Claim 16, wherein the thickness of said heat exchanger, in the direction of flow of said first fluid channels, is less than about 2.0 mm.

Claim 19 (original): A heat exchanger as recited in Claim 16, wherein the thickness of said heat exchanger, in the direction of flow of said first fluid channels, is less than about 1.0 mm.

Claim 20 (original): A heat exchanger as recited in Claim 16, wherein said heat exchanger has a density of said first fluid channels greater than about 200 per square centimeter.

Claim 21 (original): A heat exchanger as recited in Claim 16, wherein the thickness of said heat exchanger, in the direction of flow of said first fluid channels, is less than about 1.0 mm; and wherein said heat exchanger has a density of said first fluid channels greater than about 200 per square centimeter.

Claim 22 (original): A heat exchanger as recited in Claim 16, wherein said heat exchanger is fabricated from a polymer.

Claim 23 (original): A heat exchanger as recited in Claim 16, wherein said heat exchanger is fabricated from copper.

13
ent
Claim 24 (original): A heat exchanger as recited in Claim 16, wherein said heat exchanger is fabricated from aluminum.

Claim 25 (original): A heat exchanger as recited in Claim 16, wherein said heat exchanger is fabricated from metal.

Claim 26 (original): A heat exchanger as recited in Claim 16, wherein said heat exchanger is fabricated from a copper alloy.

Claim 27 (original): A heat exchanger as recited in Claim 16, wherein said heat exchanger is fabricated from a nickel-boron alloy.

Claim 28 (original): A method for fabricating a cross flow heat exchanger as recited in Claim 16, said method comprising the steps of:

(a) manufacturing a polymer sheet having a plurality of holes traversing the sheet, wherein the portions of the sheet containing polymer correspond to the one or more second fluid channels, and wherein the holes correspond to the first fluid channels;

(b) plating at least one layer of metal on the surfaces of the polymer sheet, including plating metal on the walls of the holes, but without completely filling the holes with metal; and

(c) removing the polymer without removing the metal;

(d) whereby the metal structure remaining after removal of the polymer is a cross flow heat exchanger as recited in Claim 16, wherein the spaces in the metal structure where the polymer previously had been become the one or more second fluid channels, and wherein the holes that originally traversed the polymer sheet become the first fluid channels.

Claim 29 (original): A method as recited in Claim 28, additionally comprising the step of manufacturing the polymer sheet by x-ray lithography or by the LIGA process.

Claim 30 (original): A method as recited in Claim 28, wherein said sheet comprises poly(methyl methacrylate).

Claim 31 (original): A method as recited in Claim 28, wherein said removing step comprises dissolving the polymer.

Claim 32 (original): A method as recited in Claim 28, wherein said removing step comprises melting the polymer.

Claim 33 (original): A method as recited in Claim 28, wherein said plating step comprises electrode-less plating of a metal layer.

173
6/17
Claim 34 (original): A method as recited in Claim 33, wherein said electrode-less plating step comprises first, sputtering onto the polymer sheet a first metal layer having a thickness about 1 μm thick or less, and second, catalytically depositing onto the first metal layer a second metal layer having a thickness between about 25 μm and about 150 μm .

Claim 35 (new): A heat exchanger as recited in Claim 1, wherein said heat exchanger is fabricated from nickel.

Claim 36 (new): A heat exchanger as recited in Claim 16, wherein said heat exchanger is fabricated from nickel.
